



TECHNICAL DATA SHEET

SAMAN GROUT SEALER UGS

Saman Grout Sealer is a non-yellowing acrylic sealer which forms a clear stain-resistant finish. It forms a protective barrier against food stains, grease, oil and mildew on floors and walls.

PRODUCT SPECIFICATIONS

pH: 8.0-8.5

Solids: 28 ± 1% (by weight); 26 ± 1% (by volume)

Viscosity: 18-20 seconds (Zahn cup #2)

Density: 1.03-1.04 kg/l

Drying times: dry to touch in 30 minutes at 70°F and 50% relative humidity. Drying time may vary according to room temperature and relative humidity.

Coverage: 300-400 sq. ft/gal.

VOC: 52 g/l

Gloss levels: 25-35% (measured at an angle of 60°)

Recommended applicators: small brush, grout sealer applicator bottle

Clean up: Clean applicator and equipment with water.

Storage: minimum temperature 41°F, maximum temperature 95°F. Freeze-thaw stable (if frozen, thaw completely before using). KEEP OUT OF REACH OF CHILDREN.

Shelf life: at least 1 year in a well closed container.

APPLICATION

Surface preparation

1. New grout: Allow to cure for at least 72 hours prior to application.
2. Old grout: Clean with Ultimate Grout Cleaner and allow to well dry.

Testing

Always do a test area to determine whether desired results will be achieved.

Finish application

Allow the product to reach room temperature before application. Apply the product at room temperature between 60 and 80 °F with a relative humidity rate between 30 and 80%.

1. Mix thoroughly by gently stirring. Do not shake.
2. Apply on grout lines. Be careful to avoid getting any sealer on tile. If sealer gets on tile, wipe off immediately.
3. Allow to dry.

Curing

Surfaces are useable 24 hours after application.

To the best of our knowledge, the information contained herein is accurate. Since conditions and methods are beyond our control, no warranty is expressed or implied as for the final result. The user is advised to access the suitability of the product on a test area before application.