

CONCRETE PREPARATION ETCHER

1. Identification

Product identifier:	CONCRETE PREPARATION ETCHER
Product code:	UCP
Supplier Name:	SamaN
	660 Rue du Filtre
	Victoriaville, Québec
	G6T 0T6
Telephone:	819 751-2350
Emergency telephone number:	819-751-2350
Available hours:	8h-17h
Recommended use:	To clean concrete, bricks, pavers, slabs, masonry as well as stucco.
Restrictions on use:	Do not apply to copper, galvanized steel or aluminum.

2. Hazard identification



Hazard statement(s): Causes severe skin burns and eye damage. Causes serious injury to the respiratory tract.

Precautionary statement(s)

Prevention: Wear protective gloves, protective clothing and eye protection/face protection. Do not breathe mist, vapours and spray. Wash thoroughly after handling.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for



CONCRETE PREPARATION ETCHER

several minutes. Remove contact lenses if present and easy to do. Continue rinsing. In all cases, immediately call a POISON CENTER/doctor. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse.

Disposal: Store locked up.

Storage: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: No other effects shown.

See toxicological information, section 11

3. Composition/Information on ingredients

No	CAS no	Common name and synonyms	Concentration (W/W)
1	7664-38-2	Phosphoric acid	28.00%

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.



CONCRETE PREPARATION ETCHER

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Symptoms: This product is irritating and corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). Cough, breathing pain, redness, edema and paresthesia.

Effects (acute or delayed): Ingestion may cause severe burns to the mouth and digestive tract with possible perforation of the esophagus and stomach. Inhalation of high concentrations vapors can cause severe burns to the mouth and airways leading to the lungs. If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness.

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: May release dangerous fumes.

Hazardous combustion products: Phosphorus oxide.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



CONCRETE PREPARATION ETCHER

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosionproof equipment. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. The handling of this product must comply with local regulations. Store in an airtight container located in a dry, well ventilated and soil corrosion resistant cemented. Refer to the storage of the ROHS standards and NFC. Keep away from combustible materials and bases. If the product is stored with other dangerous substances, refer to the NFC segregation table. Containers for corrosive substances shall be kept closed, carry clear identification of their contents and be handled with care. Note: this product attacks certain types of plastic, rubber or coating.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Finely divided metals (Ba, Be, Na, P, Al, Mg etc). Bases.



CONCRETE PREPARATION ETCHER

8. Exposure controls/Personal protection

No	CAS no	CAS name	IDHL mg/m3	TWA mg/m3	STEL mg/m3	CEIL mg/m3
1	7664-38-2	Phosphoric acid	4008	1	3	Not available

IDHL: Immediately Dangerous to Life or Health Concentrations TWA : Time Weighted Average STEL: Short -Term Exposure Limit CEIL: Ceiling Limit

IPVS = Inmediatamente peligroso para la vida o la salud VEPP = Valor de exposición promedio ponderado VECD = valor de exposición de corta duración VL = valor límite

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.



CONCRETE PREPARATION ETCHER

9. Physical and chemical properties

Physical state: Liquid Colour: Colourless Odour: Odorless Odour threshold: Not applicable **pH:** 1 Melting/Freezing point: 0°C (32°F) Initial boiling point/boiling range: 100°C (212°F) Flash point: Not applicable Lower flammable/explosive limit: Not applicable Upper flammable/explosive limit: Not applicable Auto-ignition temperature: Not applicable Evaporation rate: 0,05 (ether=1) Vapour pressure: 17,00 mm Hg at 20 °C Vapour density: < 1 (air =1) Relative density: 1,581 kg/L à 20 °C (water = 1) Solubility in water: Soluble Partition coefficient - n-octanol/water: Not applicable Decomposition temperature: Not available Kinematic viscosity: Not available

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use.

Possibility of hazardous reactions: No dangerous or polymerization reactions will not occur under normal conditions of use.

Conditions to avoid: Keep away from incompatible products.

Incompatible materials: This product may attacks metals.

Hazardous decomposition products: Phosphorus oxide.



CONCRETE PREPARATION ETCHER

11. Toxicological information

No	CAS no	CAS name	(1) LD	(2) LD	(3) LD	(4) LC	(5) LC	(6) LC
			oral	skin	skin	gases	vapours	dusts-mist
1	7664-38-2	Phosphoric acid	1250	Not	2740	Not	Not	>5,00
				available		applicable	applicable	

- (1) LD₅₀ oral mg/kg
- (2) LD₅₀ skin mg/kg
- (3) LD₅₀ skin mg/kg
- (4) LC₅₀ inhalation ppmV 4h gases
- (5) LC_{50} inhalation mg/l 4h vapours
- (6) LC₅₀ inhalation mg/l 4h dusts-mist

Routes of exposure: This product is not absorbed in the body, it exerts a local action that destroys tissue.

Symptoms: This product is irritating and corrosive to skin, eyes, respiratory and digestive tracts. The severity of symptoms can vary depending on the exposure conditions (contact time, product concentration, etc.). Cough, breathing pain, redness, edema and paresthesia.

Delayed and immediate effects: Ingestion may cause severe burns to the mouth and digestive tract with possible perforation of the esophagus and stomach. Inhalation of high concentrations vapors can cause severe burns to the mouth and airways leading to the lungs. If on skin, this product causes severe burns. Contact with eyes may cause redness, tearing, edema, pain, corneal opacity and even blindness.

No	CAS no	CAS name	IARC	ACGIH	Mutagenicity	Effect on
						reproduction
1	7664-38-2	Phosphoric acid	4	A5	No effects shown.	Not available.

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.
Group 2A: probably carcinogenic to humans.
Group 2B: possibly carcinogenic to humans.
Group 3: not classifiable as to its carcinogenicity to humans.
Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)



CONCRETE PREPARATION ETCHER

Group A1: confirmed human carcinogen.

Group A2: suspected human carcinogen.

Group A3: confirmed animal carcinogen with unknown relevance to humans.

Group A4: not classifiable as a human carcinogen.

Group A5: not suspected as a human carcinogen.

12. Ecological information

No	CAS no	CAS name	%	Persistant	Bio-accumulation	Aquatic
						ecotoxicity
1	7664-38-2	Phosphoric acid	28.00	Yes	No	No

No	CAS no	CAS name	%	Ecotoxicity for	Ecotoxicity for	Environnemental
				aquatic	aquatic	effects
				organisims-Short	organisims-Long	
				term	term	
1	7664-38-2	Phosphoric acid	28.00	No known	No known	No known
				adverse effect to	adverse effect to	adverse effect to
				aquatic life.	aquatic life.	the environment.

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.



CONCRETE PREPARATION ETCHER

14. Transport information

	TDG	DOT	IMDG	ΙΑΤΑ
UN number	1805	1805	1805	1805
Proper shipping name	PHOSPHORIC ACID	PHOSPHORIC ACID	PHOSPHORIC ACID	PHOSPHORIC ACID
	SOLUTION	SOLUTION	SOLUTION	SOLUTION
Transport hazard class(es)	8	8	8	8
Packing group	Ш	III	111	111

Other information

Marine pollutant: No

IMDG: Not applicable

Exemption for limited quantity: 5L

In accordance with the Canadian Transport of Dangerous Goods regulations by Road, we use the 1.17 exemption when applicable.

Special precautions: Not applicable

Others exemptions: No other exemption.

15. Regulatory information

Canada

No	CAS	CAS name	%	DSL	NDSL	NPRI
1	7664-38-2	Phosphoric acid	28.00	Х		

United-States

No	No CAS	Nom CAS	%	TSCA	PROP-65	Right to Know
1	7664-38-2	Phosphoric acid	28.00	Х		Х

All ingredients are listed on the EINECS or in compliance with the inventory.

The customer is responsible for determining the PPE (personal protection equipment) code for this material.

The classification of the product and the SDS were developped in accordance with HPR.



CONCRETE PREPARATION ETCHER

16. Other information

Date: 2018-07-20 Version: 1

Notice to the reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material suppliers'. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.