EASY WIPE ON APPLICATION

- Usages: Recommended for use on all interior wood surfaces including paneling, woodwork, hardwood floors, wood furniture, window frames....
- Preparing Your Surfaces: Apply only to bare or newly stained woods. Remove any old finishes, wax, grease or polishes. Wood should be sanded smooth following the wood grain direction ending with fine #120 grit sandpaper, for floors end with #150 grit. Remove all sand dust.

This step is essential to obtain good results!

■ Application: Shake thoroughy to evenly mix the color pigments in the oil. The finish will have a slight amber color, and should be tested in an inconspicuous area to determine the desired color and final effect. Simply wipe it on with a soft cloth or cotton blend. Allow to penetrate 5-10 minutes. Wipe off any excess. Allow to dry 6-8 hours.

NEVER LET A COAT DRY WITHOUT REMOVING THE EXCESS OR POLISHING THE SURFACE.

The application of a varnish is not needed, however, if a higher sheen is required, SamaN waterbased varnish can be applied after 7 days.

- **V.O.C.** 7g/L
- Coverage: One quart (1L) covers up to 300 sq. ft. (28m²) depending upon wood porosity. Do not thin.
- **Storage:** Store at room temperature
- Cleanup and Disposal: Clean brushes and equipment with SamaN Oil and Wax Remover.



ALL NATURAL OILS

BEAUTIFY AND PROTECT FLOORS - FURNITURE - FINE WOOD

Low odor U.V. Protection Dries Fast

DANGER OF COMBUSTION

Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Keep out of reach of children

As the conditions in which our product is used are beyond our control, we can only guarantee that it fully complies with our standards of quality and that the responsibility of the manufacturer, if applicable, is limited to the purchase price of the product.

